
PCB Power Relay







Model		L91H				
Features	Dimension L* W * H (mm)	32.4 * 27.6 * 28				
	Terminal Type	РСВ				
	Weight	35gm approximately				
Contact Data	Contact Form	10				
	Contact Material	Ag Alloy				
	Contact Capacity	NO:- 45A @240VAC NC:- 30A @240VAC				
	Contact Resistance	100mΩ Max. (at 1A / 24VDC)				
Coil Data	Coil Voltage	12VDC & 24VDC				
	Coil Power Consumption	0.9W				
	Coil Specification	Coil Voltage	Coil Resistance (2) ±10%	Pull in Voltage Max. (VDC)	Drop Out Voltage Min. (VDC)	
		12VDC	160	75%	10%	
		24VDC	660	75%	10%	
General Data		1500VAC (Between open Contacts)				
	Dielectric Strength	2500VAC (Betw	2500VAC (Between coil & Contacts)			
	Insulation Resistance	100MΩ @500VDC				
	Operate Time	15ms				
	Release Time	10ms				
Dimension	77.5 3.08 3.6 3.6 3.6 3.6 3.6 3.6 4	1 F	(Bottom view) (Top vie	± 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	3-02.1 0 0 0 2.01.	
Application	Television, Stereo, Microwave,	levision, Stereo, Microwave, Air Conditioner, Refrigerator, Iron, Electrical Boiler, Satellite Receiver, etc.				