



LZH3 - DC5V - S - H

Relay Type:-
Coil Voltage:- 3 ~ 24VDC
Type of Sealing:- S: Plastic Sealed Type
Coil Power:- 0.2W

Model		LZH3			
Features	Dimension L * W * H (mm)	15.5 * 10.5 * 11.8			
	Terminal Type	PCB			
	Weight	3.5g Approximately			
Contact Data	Contact Form	1C			
	Contact Material	Ag Alloy			
	Contact Capacity	3A @250VAC / 3A @30VDC			
	Contact Resistance	100mΩ Max. (at 1A / 6VDC)			
Coil Data	Coil Voltage	3 ~ 24VDC			
	Coil Power Consumption	0.2W			
	Coil Specification	Coil Voltage	Coil Resistance (Ω) ±10%	Pull in Voltage Max. (VDC)	Drop Out Voltage Min. (VDC)
		5VDC	120	75%	10%
		12VDC	720	75%	10%
24VDC		2880	75%	10%	
General Data	Dielectric Strength	500VAC (Between open Contacts)			
		1000VAC (Between coil & Contacts)			
	Insulation Resistance	100MΩ 500VDC			
	Electrical Life	1 x 10 ⁵			
	Mechanical Life	1 x 10 ⁷			
Operating Temperature	-25 °C to + 70 °C				
Dimension					
Application	Telephone, Fax Machine, Cordless Phone, Server, Modem, etc.				