



LSC3 - 12VDC - D  
 Relay Type:-  
 Coil Voltage:- 3 ~ 24VDC  
 Coil Sensitivity:- Nil:- 0.36W  
 D:- 0.20W

Model		LSC3			
Features	Dimension L * W * H (mm)	15.5 * 10.5 * 11.5			
	Terminal Type	PCB			
	Weight	3.5 gm Approximately			
Contact Data	Contact Form	1C			
	Contact Material	AgCdO			
	Contact Capacity	3A @ 220VAC, 3A @ 30VDC			
Coil Data	Coil Voltage ( DC)	3 ~ 24 VDC			
	Coil Power Consumption	0.36W / 0.2W			
	Coil Specification	Coil Voltage	Coil Resistance ( $\Omega$ ) $\pm 10\%$	Pull in Voltage (VDC)	Drop Out Voltage(VDC)
		5 VDC	70 / 120	75 %	10 %
		12 VDC	400 / 720	75 %	10 %
24 VDC		1600 / 2880	75 %	10 %	
General Data	Dielectric Strength	500 VAC @ 50 Hz / Min (Between Open Contacts)			
		1000 VAC @ 50 Hz / Min ( Between Coil & Contacts)			
	Insulation Resistance	100 M $\Omega$			
	Electrical Life	$1 \times 10^5$			
	Mechanical Life	$1 \times 10^7$			
Operating Temperature	- 25 °C ~ + 70 °C				
Mounting Diagram					
Application	Telecom, EPABX, Security System etc.				